



Safe Work Procedure

LAWN MOWER (PUSH)

Safe Work Procedure		LAWN MOWER (PUSH)	
Department / Area:	Approved By:	Date Created:	Review / Revised date:
Plant Operations	Program Lead Plant Operations	February 28, 2014	
Potential Hazards:		Personal protective equipment / devices	
Fill in those that apply		required / other safety considerations	
H       M       L       risk for injury         Awkward / sustained postures – forward lean         Forceful exertions – thick grass, uneven terrain         Vibration – hand arm, increases with time         Surfaces causing slips / falls         Extreme heat         Noise         Combustibles / flammables- gas, oil         Rotating blades, debris thrown from blades		<ul> <li>-Hearing protection</li> <li>-No electronic devices when operating mower</li> <li>-Appropriate closed toe footwear</li> <li>-Wear long pants</li> </ul> Training / Reference information -Module 1 SCHIPP Orientation -Department Orientation -Operator's manual	
Note: Signs and symptoms of a musculoskeletal injury (MSI) can include pain, burning, swelling, stiffness, numbness/tingling, and/or loss of movement or strength in a body part. Report these to your supervisor.         Employers must ensure that workers are trained and follow this safe work procedure Steps to perform this task safely:         -Ensure all shields and guards such as rear drag shield including discharge deflector are in place and working properly.         -Avoid unnecessary engine idling in enclosed spaces such as sheds or garages.         -Avoid mowing areas close to where people are present.         -Make best efforts to clear the area to be mowed of any debris which could be thrown from the blades. Watch for hidden hazards such as holes, roots, drain pipes, or insect nests. Use caution around low hanging branches and shrubs.         -Only reach under the machine when it is turned off and blades have stopped turning.         -Do not touch hot motor parts or spray cold water on a hot engine.         -Do not take wheel height adjustments, unclog chute, remove grass catcher, or refuel while the engine is running.         -Do not leave a running mower unattended.         -Refuel in a well ventilated, level area and allow engine to cool at least 10 minutes or as per operating manual prior to refueling.         When leaving the machine:         -Disengage power to the blade			
-Stop the engine			