



Safe Work Procedure

Safe Work Procedure		YARD TRACTOR & ATTACHMENTS	
Department / Area:	Approved By:	Date Created:	Review / Revised date:
Plant Operations	Program Lead Plant Operations	February 28, 2014	
Potential Hazards:		Personal protective equipment / devices	
Fill in those that apply		required / other safety considerations	
H M L risk for injury Awkward / sustained postures – slouched sitting Vibration - (whole body) increases with time Pinch points-attaching/detaching equipment Materials falling-material in loader bucket		-Hearing protection -No electronic devices when operating tractor	
		-Appropriate closed toe footwear	
		-No passenger permitted	
Moving machinery – blades / belts/ pto, etc.		-Never make modifications to disconnect any	
Extreme heat / cold		manufacturer safety features	
Chemicals- acid battery Noise Combustibles / flammables- fuel Debris thrown from equipment		Training / Reference information	
		Training / Reference information	
		-Module 1 SCHIPP Orientation	
		-Department Orientation	
		-Operator`s manual	
Note: Signs and symptoms of a musculoskeletal injury (MSI) can include pain, burning, swelling, stiffness,			
numbness/tingling, and/or loss of movement or strength in a body part. Report these to your supervisor.			
Employers must ensure that workers are trained and follow this safe work procedure			
Steps to perform this task safely:			
Note: Attachments may include but are not limited to: snow blowers, sweeper, tiller, mower, trailers, blade and loader.			
-Ensure all shields and guards including discharge deflector are in place and working properly.			
- Ensure the tractor's safety reflector is in place on the tractor.			
-Avoid unnecessary engine idling in enclosed spaces such as sheds or garages.			
-Avoid or take extra caution when working in areas close to where people are present.			
-Disengage power to attachments if you must drive over surfaces such as gravel.			
-Make best efforts to clear the area to be mowed/swept or blown of any debris which could be thrown from the blades.- Watch for hidden hazards such as holes, roots, drain pipes, or insect nests.			
- Use caution around low hanging branches and shrubs.			
-Drive up and down slopes at a partial angle on steep slopes rather than across them to reduce the risk for tippingOnly work on attachments when power is turned off, key removed and moving equipment has stopped.			
-Do not touch hot motor parts or spray cold water on a hot engineTurn off power to tractor and equipment prior to any maintenance such as unclogging chutes, removing grass catcher,			
or refueling.			
-Do not leave tractor or equipment unattended when running.			
-Refuel in a well ventilated area. Allow time to cool as per Operator's manual before refuelling.			
When leaving the machine -Disengage power to the a -Stop the engine -Set park brake	ıttachment		
-Remove key and return it to the designated area			