



Safe Work Procedure		Pallet Jack (Electric) and Pallet Handling	
Department / Area: Physical Plant Services	Approved By: Regional Manager of Physical Plant Services	Date Created: September 5 2014	Review Date: Revised date:
Potential Hazards:         Fill in those that apply         H       M       L       Risk for Injury         Sharp Points / Edges – rough or splintered wood         Pinch Points – jamming fingers or toes         Awkward / sustained postures – bending, twisting         Forceful exertions – lifting / pushing heavy pallets         Chemical - battery		<ul> <li>Personal protective equipment / devices required / other safety considerations:</li> <li>Appropriate closed toe footwear</li> <li>Gloves to protect against cuts/slivers/pinches when handling pallets is recommended</li> <li>Ensure path is clear of obstacles prior to moving pallet</li> <li>Two people if lifting pallet</li> <li>Training / Reference Information:</li> <li>SCHIPP Module 1 training</li> <li>Department Orientation</li> <li>Operator's Manual</li> </ul>	
Note: Signs and symptoms of a mus and/or loss of movement or strength Employers must ensure that worke Steps to perform this task safely:	in a body part. Report these to	your supervisor.	ess, numbness/tingling,
Pallet Jack Operation			
Read Operator's Manual			
Operate jack with back straight and elbows at sides.			
Ensure your pallet jack weight capacity can handle the load.			
Only one operator of a pallet jack.			
Start the pallet jack slowly.			
Never ride a pallet jack.			
Never leave a pallet jack with the load elevated.			
Stack the pallet load so that it will not shift or turn over when moving load.			
Pallet Stacking			
Pallets should be stacked flat in most situations.			
Pallets that will be manually removed from a pile are to be stacked no more than 8 pallets high.			
<ul> <li>Any stack over 8 pallets high requires a lift to remove a pallet.</li> <li>Pallets being removed from a pile 8 high or less are to be removed in the following manner:</li> </ul>			
<ul> <li>Slowly push the pallet away from you or pull it toward you over the pallet beneath it.</li> <li>Continue sliding the pallet while tilting the side that is furthest off the pallet toward the ground.</li> </ul>			
Keep your hands and feet away from pinch points and when bending over, maintain a wide stance, bend your knees and			

- > Once the pallet touches the ground, tilt up the other side, move behind it and slide it to where it is required.
- > Lower the side of the pallet toward you until it is on the ground. Use proper lifting procedure as above.
- > No pallet should be lifted off the ground by one worker. If a pallet has to be lifted manually, a minimum of 2 workers are required.
- To lift a pallet with 2 workers, each on opposite ends and bend their knees and hips to reach the pallet. Each worker grasps a pallet cross brace with both hands. On a designated count by one worker, both workers lift the pallet by pushing through the legs while keeping their backs as straight as possible and shoulders neutral. Do not twist your body when carrying a pallet. Take small steps to turn.