



Safe Work Procedure		Yard Tractor and Attachments	
Department / Area: Physical Plant Services	Approved By: Regional Manager of Physical Plant Services	Date Created: September 5 2014	Review Date: Revised date:
Potential Hazards: Fill in those that apply H M L Risk for Injury Moving machinery – blades / belts / pto, etc. Combustibles / flammables - fuel Noise Debris thrown from equipment Awkward / Sustained postures – slouched sitting Vibration (whole body) – increases with time Extreme Heat / Cold Pinch Points – attaching / detaching equipment Materials Falling – material in loader bucket Chemicals – battery acid		Personal protective equipment / devices required / other safety considerations: Eye Protection / Goggles Hearing Protection Appropriate closed toe footwear No passengers permitted No electronic devices when operating tractor Never make modifications to disconnect any manufacturer safety features Training / Reference Information: Department Orientation Operator's Manual MSDS Training	
Note: Signs and symptoms of a musculoskeletal injury (MSI) can include pain, burning, swelling, stiffness, numbness/tingling, and/or loss of movement or strength in a body part. Report these to your supervisor. Employers must ensure that workers are trained and follow this safe work procedure. Steps to perform this task safely:			
 Ensure all shields and guards, including discharge deflector, are in place and working properly. Ensure the tractor's safety reflector is in place on the tractor. Avoid unnecessary engine idling in enclosed spaces such as sheds or garages. Avoid or take extra caution when working in areas close to where people are present. Install barrier and signage if required. Disengage power to attachments if you must drive over surfaces such as gravel. Make best efforts to clear the area to be mowed / swept or blown of any debris which could be thrown from the blades. Watch for hidden hazards such as holes, roots, drain pipes, or insect nests. Use caution around low hanging branches and shrubs. Drive up and down slopes at a partial angle on steep slopes rather than across them to reduce risk for tipping. Only work on attachments when power is turned off, key removed. and moving equipment has stopped. Do not touch hot motor parts or spray cold water on a hot engine. Turn off power to tractor and equipment prior to any maintenance such as unclogging chutes, removing grass catcher, or refueling. 			
 Do not leave tractor or equipment unattended when running. Refuel in a well-ventilated area. Allow time to cool as per Operator's Manual before refueling. When Leaving the Machine: Disengage power to the attachment. Stop the engine. Set Park Brake. Demonstrate to the designated area. 			

Remove key and return it to the designated area.